

COLORado™ 2 IP

SPECIFICATIONS & FEATURES

CHAUVET®



AT A GLANCE:

RGBW Color Mixing



Key Features:

- RGBW Color Mixing
- 5 Distinct Dimming Curves
- Color temperature presets
- IP66 Rated



About this light:

The COLORado™ 2 IP indoor/outdoor color wash is fitted with 48 high powered 2- to 3-watt LEDs including white for more precise color temperature control and to produce a nearly limitless color range.

The sturdy die cast aluminum body, rated at IP-66, makes it suitable for indoor and outdoor applications. This fixture runs on DMX as well as onboard customizable programs. It is also compatible with the COLORado™ Controller..

DETAILED SPECIFICATIONS:

FEATURES

- DMX connectors: 3-pin
- Source: 48 (2 and 3 W) LEDs, 50,000 hours
- Configuration: 12 red (700 mA), 12 green (1,000 mA), 12 blue (1,000 mA), 12 white (1,000 mA)
- Installed Optic(s): 15°
- Beam Angle: 11°
- Field Angle: 23°
- Lux: 2,798 @ 5 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 180 W, 1.43 A (operating)
- Power Consumption 230 V, 50 Hz: 179 W, 0.78 A (operating)
- Power linking: 7 units @ 120 V / 14 units @ 230 V
- Dimensions: 9 x 11.9 x 10.9 in (230 x 303 x 276 mm)
- Weight: 20 lbs (9.1 kg)
- Power Connection: Edison to proprietary IP66 input power cord (65 in / 1,651 mm)
- Control Connection: 3-pin DMX to proprietary IP66 input cable (6.5 in / 165 mm)
- Certification: CE, ETLc
- Environment: IP66, outdoor/wet, with pressure equalizing M12 GORE® valve
- Optics: 30° lenses, color blending filters (1°, 5° or 10°)
- Cabling: 16.5 ft (5 m) signal extension, 16.5 ft (5 m) power extension

SPECIFICATIONS

- DMX connectors: 3-pin
- Source: 48 (2 and 3 W) LEDs, 50,000 hours
- Configuration: 12 red (700 mA), 12 green (1,000 mA), 12 blue (1,000 mA), 12 white (1,000 mA)
- Installed Optic(s): 15°
- Beam Angle: 11°
- Field Angle: 23°
- Lux: 2,798 @ 5 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 230 V, 50 Hz: 179 W, 0.78 A (operating)
- Power linking: 14 units @ 230 V
- Dimensions: 230 x 303 x 276 mm
- Weight: 9.1 kg
- Power Connection: Edison to proprietary IP66 input power cord (1,651 mm)
- Control Connection: 3-pin DMX to proprietary IP66 input cable (165 mm)
- Certification: CE, ETLc
- Environment: IP66, outdoor/wet, with pressure equalizing M12 GORE® valve

www.chauvetlighting.com
www.chauvetlighting.co.uk

CHAUVET®