

# COLORDash™ Accent VW & UV SPECIFICATIONS & FEATURES

CHAUVET®

## COLORDash™ Accent VW



### About this light:

The COLORDash Accent VW is a 2, 3 or 5 channel DMX LED powered variable white wash. This compact wash is perfectly suited for applications where space is an issue or the user wants to contain the wash in a small, concentrated pool. The cast aluminum housing helps dissipate heat and provides a sleek yet rugged look. Fitted with 18deg lenses the unit produces a tight, yet even wash of light. The COLORDash Accent VW can be programmed via DMX or the user can easily assign output and color temperature via the dipswitches.

### FEATURES

- DMX channels: 2, 3, or 5-channel
- Operating modes
  - 2-channel: Warm white, cool white control
  - 2-channel: Dimmer, white macros
  - 3-channel: Dimmer, warm white, cool white
  - 5-channel: Dimmer, warm white, cool white, white macros, strobe
- Colors LED: Warm White, Cool White
- Dimmer: Electronic
- Variable white mixing with or without DMX control
- Built-in automated programs via master/slave or DMX
- Double-bracket yoke doubles as floor stand

### SPECIFICATIONS

- DMX connectors: 3-pin
- Source: 7 (1 W) LEDs, 50,000 hours
- Configuration: 4 warm white (350 mA), 3 cool white (350 mA)
- Installed Optic(s): 18°
- Beam angle: 25°
- Field angle: 43.7°
- Lux: 258.33 @ 2 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 10 W, 0.1 A (operating)
- Power Consumption 230 V, 50 Hz: 10 W, 0.1 A (operating)
- Dimensions: 6.9 x 4.3 x 2.5 in (174 x 108 x 65 mm)
- Weight: 1.6 lbs (0.7 kg)
- Power Connection: Edison
- Control Connection: 3-pin DMX
- Certification: CE, ETLc
- Environment: IP20, dry location

## COLORDash™ Accent UV



### About this light:

The COLORDash Accent UV is a 1 or 2 channel DMX LED powered blacklight. This compact wash is perfectly suited for applications where space is an issue or the user wants to contain the effect in a small, concentrated pool. The cast aluminum housing helps dissipate heat and provides a sleek yet rugged look. Fitted with 18deg lenses the unit produces a tight, yet even wash of UV light that really makes fluorescing materials pop! The COLORDash Accent UV can be programmed via DMX or the user can easily assign output via the dipswitches.

### FEATURES

- DMX channels: 1 or 2 channel
- Operating modes
  - 1-channel: dimmer control
  - 2-channel: dimmer, strobe control
- Dimmer: Electronic
- UV intensity with or without DMX control
- Built-in automated programs via master/slave or DMX
- Double-bracket yoke doubles as floor stand

### SPECIFICATIONS

- DMX connectors: 3-pin
- Source: 7 (1 W) LEDs, 50,000 hours
- Configuration: 2 red (350 mA), 2 green (350 mA), 2 blue (350 mA), 1 white (350 mA)
- Installed Optic(s): 18°
- Beam angle: 20°
- Field angle: 37.5°
- Lux: N/A
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 10 W, 0.1 A (operating)
- Power Consumption 230 V, 50 Hz: 10 W, 0.1 A (operating)
- Dimensions: 6.9 x 4.3 x 2.5 in (174 x 108 x 65 mm)
- Weight: 1.5 lbs (0.6 kg)
- Power Connection: Edison
- Control Connection: 3-pin DMX
- Certification: CE, ETLc
- Environment: IP20, dry location

[www.chauvetlighting.com](http://www.chauvetlighting.com)  
[info@chauvetlighting.com](mailto:info@chauvetlighting.com)

CHAUVET®