



Q-SPOT™ 260-LED



FEATURES

- DMX channels: DMX channels: 11 or 14
- Pan: 540°
- Tilt: 270°
- Colors Wheel: 8, continuous scroll at variable speeds
- Gobo wheel (static): 9, interchangeable, continuous scroll at variable speeds
- Gobo wheel (rotating): 7 (5 metal + 2 glass), interchangeable, slot-n-lock, continuous scroll at variable
- 3-facet rotating prism
- Variable electronic dimmer (0 ~ 100%)
- Remote fixture reset
- Move-in-black for pan/tilt
- Built-in automated programs
- Built-in sound activated programs
- 255 user-programmable steps without DMX controller
- High-powered, 60 W LED
- User-selectable pan/tilt ranges
- Automatic pan/tilt correction
- Reset to factory settings option
- User-selectable basic or advanced operating modes
- Easy access door for gobo change

SPECIFICATIONS

- DMX connectors: 3-pin
- Pan & tilt: 540° / 270°
- Gobo size: 26mm outside, 19mm image, 2.2mm max thickness
- Source: 60 W LED, 50,000 hours
- Configuration: 1 white (12.6 A)
- Beam angle: 15°
- Lux: 750 @ 5 m
- AC Voltage Range: 100~240 V, 50/60 Hz (auto-ranging)
- Power Consumption 120 V, 60 Hz: 153 W, 1.3 A (operating)
- Power Consumption 230 V, 50 Hz: 138 W, 0.6 A (operating)
- Dimensions: 11.4 x 10.9 x 19.1 in (292 x 278 x 485 mm)
- Weight: 30 lbs (13.6 kg)
- Gobo Size: 25.8 mm outside, 18.2 mm image, 1.2 mm max thickness
- Power Connection: IEC
- Control Connection: 3-pin DMX
- Certification: CE, ETLc
- Environment: IP20, dry location

www.chauvetlighting.com
www.chauvetlighting.co.uk

CHAUVET®